







L123 S123

Spotlights


light fitting for feeding tracks or for surface assembly • rotary to 355°, tipping to 90° • integrated electronic control gear or transformer • housing of aluminium profile, separate reflector part • quality aluminium reflector • optional beam angle • colour option • protective glass or optional filter




Order code	Pict.	Source	Output	Socket	kg
L123cX1E.135/...	a	HIT-CE	1x35 W	G12	1,4
L123cX1E.170/...	a	HIT-CE	1x70 W	G12	1,4
L123cX8E.135/...	a	HIT-TC-CE	1x35 W	G8,5	1,4
L123cX8E.170/...	a	HIT-TC-CE	1x70 W	G8,5	1,4



Order code	Pict.	Source	Output	Socket	kg
S123cX1E.135/...	b	HIT-CE	1x35 W	G12	1,4
S123cX1E.170/...	b	HIT-CE	1x70 W	G12	1,4
S123cX8E.135/...	b	HIT-TC-CE	1x35 W	G8,5	1,4
S123cX8E.170/...	b	HIT-TC-CE	1x70 W	G8,5	1,4

 HIT-CE / G12

 HIT-TC-CE / G8,5

W3

S3

B3



230V-50Hz

Optional types of reflectors

[12 / 24 / 36 / 60](#)

Example of order code assembly: reflector with beam angle 42°

[L123cX8E.135/42T1.S3](#)

Optional types of glasses / filters (1,5)

[T1 / T3 / F4 / F5 / F6 / F7 / FU / F1 / F2 / F3 / F8](#)

Example of order code assembly: filter for pastry

page 256

[L123cX8E.135/42F2.S3](#)

Accessories








Tracks
page 41

L123 S123

Spotlights

light fitting for feeding tracks or for surface assembly • rotary to 355°, tipping to 90° • integrated electronic control gear or transformer • housing of aluminium profile, separate reflector part • quality aluminium reflector • optional beam angle • colour option • protective glass or optional filter



Order code

L123cX8E.135/....
L123cX8E.170/....

Pict.

a
a

Source

HIT-TC-CE
HIT-TC-CE

Output

1x35 W
1x70 W

Socket

G8,5
G8,5

kg

1,4
1,4

Order code

S123cX8E.135/....
S123cX8E.170/....

Pict.

b
b

Source

HIT-TC-CE
HIT-TC-CE

Output


1x35 W
1x70 W

Socket

G8,5
G8,5

kg

1,4
1,4

 HIT-CE / G12

W3
S3
B3



230V-50Hz

Optional types of reflectors

15 / 30 / 60

Example of order code assembly: reflector with beam angle 30°

L123cX8E.135/60T1.S3

Optional types of glasses / filters (01)

T1 / T3 / F4 / F5 / F6 / F7 / FU / F1 / F2 / F3 / F8

Example of order code assembly: filter for pastry

page 256

L123cX8E.135/60F2.S3

Accessories



Tracks
page 41

EXPLAINS

for order code assembly

1	2	3	4	5	6	7	8	9	10	
V	286	s	D2	BN	.	118	H	/	HD T3	. W1

1	GROUP AFTER ASSEMBLY			2	PRODUCT CODE	3	CONFIGURATION OF LIGHT FITTING
V	recessed	L	for track	289	type marking of fitting	s	control gear on cable (part of fitting)
S	ceiling	Z	pendant	5	type marking of insert	c	control gear on fitting (part of fitting)
N	wall	C	part of fitting	etc.		-	without control gear (or it is not part of fitting)
F	floor lamp						
4	TYPE OF LIGHT SOURCE (SOCKET)						
D2	TC-D, TC-T (G24d, GX24d)	S2	HST-CRI (GX12)	R1	QT-DE12 150W (R7s L=114,2)		
D4	TC-DEL, TC-TEL (G24q, GX24q)	X1	HIT-CE (G12)	R7	QT-DE12 100W (R7s L=75)		
G0	T16-R (2GX13)	X2	HIE-CE (E27)	Q0	QPAR16 (GU10)		
G1	TC-L (2G11)	X2	HIPAR20, HIPAR30 (E27)	Q3	QR-LP111 (G53)		
G2	TC-F (2G10)	X3	Mercury (E27)	Q5	QR-CBC51 (GU5,3)		
G3	TC-S (G23)	X4	HST (E27)	E1	LED (E14)		
G5	CFL-AR111 (GX53)	X5	HIPAR 111 (GX8,5)	E2	A60, A65 (E27)		
G7	TC-SEL (2G7)	X6	HIT-DE-CE 70W (RX7s L=114,2)	E2	R50, R63, R80 (E27)		
G8	TC-TEL (2G8)	X7	HIT-DE-CE 150W (RX7s L=132)	E2	QPAR20, 30, 38 (E27)		
S1	HST-CRI (PG12-1)	X8	HIT-TC-CE (G8,5)	E2	QT32 (E27)		
	TYPE OF LED LIGHT SOURCE		TYPE OF LED LIGHT SOURCE		COLOR RENDERING INDEX		
AC	LED COIN111 AC (230V)	L	LED plate Ra >82	I	warm white "interna" (2700 K)		
		M	LED plate Ra >92	W	warm white (3000 K)		
		C	LED COB Ra >82	C	cool white (4000 K)		
		D	LED COB Ra >92	D	daylight (5000 K)		
5	TYPE OF CONTROL GEAR			6	NUMBER AND OUTPUT LIGHT SOURCE		
	BASIC CONFIGURATION				EMERGENCY CONFIGURATION		
B	inductive	N	emergency 1h	109	1 x 9 W		
K	inductive compensated	H	emergency 3h	226	2 x 26 W		
E	electronic undimmable	F	emergency 1h with autotest	318	3 x 18 W		
M	electronic MULTIWATT	G	emergency 3h with autotest	170	1 x 70 W		
A	electronic dimmable analog 1-10V	Z	electronic address module	115	1 x 150 W, 1 x 15W		
D	electronic dimmable DALI	P	central battery system				
S	electronic dimmable DSI	J	emergency 2h	062	1 x 22 W + 1 x 40 W		
C	electronic dimmable CORRIDOR function	Q	emergency 2h with autotest	252	4 x 24 W + 4 x 39 W		
T	electronic dimmable by button 230V						
W	individually dimmable by potentiometer						
L	el. phase dimmable transformer / driver						
R	electronic transformer 230V/12V						
I	LED driver (power factor 0,9)						
7	POSSIBILITIES OF CONNECTION			8	TYPE OF REFLECTOR		
D	2-pole terminal plate	HL	smooth	HP	smooth sanded		
A	4-pole terminal plate	HK	smooth with cross louvre	1P	sanded one-side emission		
B	5-pole terminal plate	HT	smooth with radial louvre	2P	sanded double-side emission		
C	3-pole+2-pole terminal plate	HD	smooth with inner glass	TP	hammered		
Z	2-pole + 4-pole terminal plate	HM	smooth metalized (Jordan)	AC	double-asymmetric with shade		
H	3-pole Wieland	HA	smooth with asymmetric insert	12	beam angle 12°		
J	3-pole 5kV Wieland	1H	smooth one-side emission	15	beam angle 15°		
K	3-pole Wieland 2x	2H	smooth double-side emission	20	beam angle 20°		
L	5-pole Wieland	FS	facet	24	beam angle 24°		
M	5-pole Wieland 2x	FK	facet with cross louvre	30	beam angle 30°		
O	3-pole Wago	FT	facet with radial louvre	36	beam angle 36°		
P	5-pole Wago	ML	matt	60	beam angle 60°		
9	TYPE OF COVER GLASS / FILTER						
T1	tempered glass - clear	E1	acrylic glass for information plate - clear	F5	red filter		
T2	tempered glass - raster	E3	acrylic glass for information plate - opal	F6	green filter		
T3	tempered glass - opal	FU	UV filter	F7	yellow filter		
V1	convex glass - clear	F1	food filter for meat and smoked-meat products	F8	food filter for fruit and vegetables		
V3	convex glass - opal	F2	food filter for pastry	P3	prisma - opal		
A1	acrylic glass - clear	F3	food filter for fish and ice cream	M3	microprisma - opal		
A3	acrylic glass - opal	F4	blue filter				
10	COLOURED FINISH						
W1	white gloss	B3	black structure	C2	chromium matt		
W2	white matt	S1	silver gloss	CY	chromium yellow		
W3	white structure	S2	silver matt	SB	S1 / B3 - combination		
B1	black gloss	S3	silver structure	WB	W1 / B3 - combination		
B2	black matt	C1	chromium gloss				