

S289

Downlights

ceiling light fitting with integrated control gear • control gear option • quality aluminium reflector in smooth or facet finish, with cross or radial louvre • horizontal position of light sources • housing of power painted steel sheet • frame of aluminium die-cast • colour option • optional decorative elements and accessories



HL



HK



HT






FS



FK



FT



Order code	Pict.	Source	Output	Socket	kg
S289cD2B.113/..	a	TC-D	1x13 W	G24d-1	4,0
S289cD2B.118/..	a	TC-D	1x18 W	G24d-2	4,0
S289cD2B.126/..	a	TC-D	1x26 W	G24d-3	4,2
S289cD2B.213/..	a	TC-D	2x13 W	G24d-1	4,3
S289cD2B.218/..	a	TC-D	2x18 W	G24d-2	4,3
S289cD2B.226/..	a	TC-D	2x26 W	G24d-3	4,7
S289cD4E.113/..	a	TC-DEL	1x13 W	G24q-1	4,0
S289cD4E.118/..	a	TC-DEL	1x18 W	G24q-2	4,0
S289cD4E.126/..	a	TC-DEL	1x26 W	G24q-3	4,0
S289cD4M.142/..	a	TC-TEL	1x26/32/42 W	GX24q	4,0
S289cD4E.213/..	a	TC-DEL	2x13 W	G24q-1	4,0
S289cD4E.218/..	a	TC-DEL	2x18 W	G24q-2	4,0
S289cD4E.226/..	a	TC-DEL	2x26 W	G24q-3	4,0
S289cD4E.232/..	a	TC-TEL	2x32 W	GX24q-3	4,0
S289-E2.110/..	a	A60, QT32	1x100 W	E27	3,5

Optional types of reflectors

HL / HK / HT / FS / FK / FT

Example of order code assembly: [reflector smooth with cross louvre](#) [S289cD2B.113/HK.SB](#)



Other configuration of control gears for fluorescent lamps

page 248

K / A / D / S / T

Example of order code assembly: [inductive compensated](#) [S289cD2K.113/HK.SB](#)



Emergency configuration of control gears for fluorescent lamps

page 250

N / H / F / G / Z / P

Example of order code assembly: [electronic, emergency operation 1h](#) [S289cD4EN.113/HK.SB](#)



Accessories



ZSF
page 182



Complements - dimension 04



QD - 04
page 127



QP - 04
page 127



QDK - 04
page 127



QPP - 04
page 127



QKV - 04
page 127



IT
page 252

TC-D / G24d

TC-DEL / G24q

TC-TEL / GX24q

A60 / E27

QT 32 / E27

WB

SB

B1



IP20 230V-50Hz