


ACCESSORIES

suspension ZSC - H



ZSC-H ceiling three-string adjustable suspension heavy (RAL colours)



Order code	Rosette colour	Length	Cable colour	Luminaire connection
ZSC-H.-10...3	W3, ...RAL	1m	BP, WP, TR	3 - conductors
ZSC-H.-10.TR-4	W3, ...RAL	1m	TR	4 - conductors
ZSC-H.-10.TR-5	W3, ...RAL	1m	TR	5 - conductors
ZSC-H.-20...3	W3, ...RAL	2m	BP, WP, TR	3 - conductors
ZSC-H.-20.TR-4	W3, ...RAL	2m	TR	4 - conductors
ZSC-H.-20.TR-5	W3, ...RAL	2m	TR	5 - conductors
ZSC-H.-30...3	W3, ...RAL	3m	BP, WP, TR	3 - conductors
ZSC-H.-30.TR-4	W3, ...RAL	3m	TR	4 - conductors
ZSC-H.-30.TR-5	W3, ...RAL	3m	TR	5 - conductors
ZSC-H.-40...3	W3, ...RAL	4m	BP, WP, TR	3 - conductors
ZSC-H.-40.TR-4	W3, ...RAL	4m	TR	4 - conductors
ZSC-H.-40.TR-5	W3, ...RAL	4m	TR	5 - conductors
ZSC-H.-50...3	W3, ...RAL	5m	BP, WP, TR	3 - conductors
ZSC-H.-50.TR-4	W3, ...RAL	5m	TR	4 - conductors
ZSC-H.-50.TR-5	W3, ...RAL	5m	TR	5 - conductors

Example of order code assembly:

length 5m, **dark anthracite ceiling rosette**, **black PVC cable**
 length 5m, dark anthracite ceiling rosette, **clear cable, emergency**
 length 5m, dark anthracite ceiling rosette, clear cable, **DALI**

ZSC-H**D3**-50.**BP**-3
 ZSC-H**D3**-50.**TR**-4
 ZSC-H**D3**-50.**TR**-5

EXPLANATORY NOTES

for order code assembly

1	2	3	4	5	6
ZSC	-	K B3	-	50 .	TP - 5

1	TYPE OF SUSPENSION				
ZSA	ceiling solid suspension	ZVA	built-in solid suspension	ZLA	solid suspension for feeding track
ZSB	ceiling one-string adjustable suspension	ZVB	built-in one-string adjustable suspension	ZLB	one-string adjustable suspension for f. track
ZSC	ceiling three-string adj. susp. with rosette	ZVD	built-in two-string adjustable suspension	ZLD	two-string adjustable suspension for f. track
ZSD	ceiling two-string adjustable suspension	ZVE	built-in four-string adjustable suspension	ZLL	cable suspension for feeding track
ZSE	ceiling four-string adjustable suspension	ZVL	built-in cable suspension		
ZSF	ceiling four-string adj. susp. with rosette	ZVM	built-in three-string adjustable suspension		
ZSL	ceiling cable suspension				
ZSM	ceiling three-string adjustable suspension				
2	SUSPENSION MODIFICATIONS				
K	metal ceiling rosette	R	for attachment to ceiling winch		
P	plastic ceiling rosette	H	for high load		
3	COLOUR OF THE SUSPENSION / ROSETTE			3	COLOUR OF TRACK ADAPTER
	metal		plastic		
W3	white sand	B	black	B	black
S3	silver sand	W	white	G	gray
B3	black sand			W	white
D3	anthracite sand dark				
xx	optional colour according to RAL				
4	LENGTH OF SUSPENSION				
05	50cm	30	300cm	xx	optional length of suspension
10	100cm	40	400cm		
20	200cm	50	500cm		
5	COLOUR OF THE SUSPENSION				
	PVC		textile		
WP	white	WT	white		
BP	black	BT	black		
TP	transparent	xT	optional colour according to sampler		
6	CONNECTION OF LUMINAIRE				
	3 - conductors		4 - conductors		5 - conductors
3	I - non-dimmable constant current driver U - non-dimmable constant voltage driver L - phase dimmable W - dimmable using push-button on luminaire B - dimmable Casambi (Bluetooth)	4	N - emergency 1h H - emergency 3h Z - electronic address module T - dimmable using button 230V C - dimmable with CORRIDOR function 4 - two-circuit connection	5	A - dimmable analog 1-10V D - dimmable DALI X - dimmable Tunable white DALI S - dimmable DSI 5 - three-circuit connection