ACCESSORIES

suspension ZSC - H

W3
S3
D3
B3

ZSC-H ceiling three-string adjustable suspension heavy (RAL colours)



Order code	Rosette colour	A	Cable colour	Luminaire connection
ZSC-H..-10...-3	W3, ... RAL	1m	BP, WP, TP	3 - conductors
ZSC-H..-10...-4	W3, ... RAL	1m	BP, WP, TP	4 - conductors
ZSC-H..-10.TP-5	W3, ... RAL	1m	TP	5 - conductors
ZSC-H..-20...-3	W3, ... RAL	2m	BP, WP, TP	3 - conductors
ZSC-H..-20...-4	W3, ... RAL	2m	BP, WP, TP	4 - conductors
ZSC-H..-20.TP-5	W3, ... RAL	2m	TP	5 - conductors
ZSC-H..-30...-3	W3, ... RAL	3m	BP, WP, TP	3 - conductors
ZSC-H..-30...-4	W3, ... RAL	3m	BP, WP, TP	4 - conductors
ZSC-H..-30.TP-5	W3, ... RAL	3m	TP	5 - conductors
ZSC-H..-40...-3	W3, ... RAL	4m	BP, WP, TP	3 - conductors
ZSC-H..-40...-4	W3, ... RAL	4m	BP, WP, TP	4 - conductors
ZSC-H..-40.TP-5	W3, ... RAL	4m	TP	5 - conductors
ZSC-H..-50...-3	W3, ... RAL	5m	BP, WP, TP	3 - conductors
ZSC-H..-50...-4	W3, ... RAL	5m	BP, WP, TP	4 - conductors
ZSC-H..-50.TP-5	W3, ... RAL	5m	TP	5 - conductors

Example of order code assembly:

length 5m, **dark anthracite ceiling rosette, black PVC cable**	ZSC-H**D3**-50.**BP**-3
length 5m, dark anthracite ceiling rosette, **clear cable**, **emergency**	ZSC-HD3-50.**TP-4**
length 5m, dark anthracite ceiling rosette, clear cable, **DALI**	ZSC-HD3-50.TP-**5**

EXPLANATORY NOTES

for order code assembly

1		2	3		4		5		6
ZSC	**-**	**K**	**B3**	**-**	**50**	**.**	**TP**	**-**	**5**

1	TYPE OF SUSPENSION				
ZSA	ceiling solid suspension	ZVA	built-in solid suspension	ZLA	solid suspension for feeding track
ZSB	ceiling one-string adjustable suspension	ZVB	built-in one-string adjustable suspension	ZLB	one-string adjustable suspension for f. track
ZSC	ceiling three-string adj. susp. with rosette	ZVD	built-in two-string adjustable suspension	ZLD	two-string adjustable suspension for f. track
ZSD	ceiling two-string adjustable suspension	ZVE	built-in four-string adjustable suspension	ZLL	cable suspension for feeding track
ZSE	ceiling four-string adjustable suspension	ZVL	built-in cable suspension		
ZSF	ceiling four-string adj. susp. with rosette	ZVM	built-in three-string adjustable suspension		
ZSL	ceiling cable suspension				
ZSM	ceiling three-string adjustable suspension				
2	SUSPENSION MODIFICATIONS				
K	metal ceiling rosette	R	for attachment to ceiling winch	S	for higher load
P	plastic ceiling rosette	H	for high load		
3	COLOUR OF THE SUSPENSION / ROSETTE			**3**	COLOUR OF TRACK ADAPTER
	metal		**plastic**		
W3	white sand	B	black	B	black
S3	silver sand	W	white	G	gray
B3	black sand			W	white
D3	anthracite sand dark				
xx	optional colour according to RAL				
4	LENGTH OF SUSPENSION				
05	50cm	30	300cm	xx	optional length of suspension
10	100cm	40	400cm		
20	200cm	50	500cm		
5	COLOUR OF THE SUSPENSION				
	PVC		**textile**		
WP	white	WT	white		
BP	black	BT	black		
TP	transparent	xT	optional colour on request		
6	CONNECTION OF LUMINAIRE				
	3 - conductors		**4 - conductors**		**5 - conductors**
3	non-dimmable constant current driver	4	emergency 1h	5	dimmable analog 1-10V
	non-dimmable constant voltage driver		emergency 3h		dimmable DALI
	phase dimmable		electronic address module		dimmable Tunable white DALI
	dimmable using push-button on luminaire		dimmable using button 230V		dimmable DSI
	dimmable Casambi (Bluetooth)		dimmable with CORRIDOR function		three-circuit connection
			two-circuit connection		