


ACCESSORIES

suspension ZSD - H



ZSD-H ceiling two-string adjustable suspension heavy (RAL colours)

Order code	Rosette colour	A	Cable colour	Luminaire connection
ZSD-H.-10...-3	W3, ... RAL	1m	BP, WP, TR	3 - conductors
ZSD-H.-10.TR-4	W3, ... RAL	1m	TR	4 - conductors
ZSD-H.-10.TR-5	W3, ... RAL	1m	TR	5 - conductors
ZSD-H.-20...-3	W3, ... RAL	2m	BP, WP, TR	3 - conductors
ZSD-H.-20.TR-4	W3, ... RAL	2m	TR	4 - conductors
ZSD-H.-20.TR-5	W3, ... RAL	2m	TR	5 - conductors
ZSD-H.-30...-3	W3, ... RAL	3m	BP, WP, TR	3 - conductors
ZSD-H.-30.TR-4	W3, ... RAL	3m	TR	4 - conductors
ZSD-H.-30.TR-5	W3, ... RAL	3m	TR	5 - conductors
ZSD-H.-40...-3	W3, ... RAL	4m	BP, WP, TR	3 - conductors
ZSD-H.-40.TR-4	W3, ... RAL	4m	TR	4 - conductors
ZSD-H.-40.TR-5	W3, ... RAL	4m	TR	5 - conductors
ZSD-H.-50...-3	W3, ... RAL	5m	BP, WP, TR	3 - conductors
ZSD-H.-50.TR-4	W3, ... RAL	5m	TR	4 - conductors
ZSD-H.-50.TR-5	W3, ... RAL	5m	TR	5 - conductors

Example of order code assembly:

length 5m, **dark anthracite ceiling rosette, black PVC cable**
 length 5m, dark anthracite ceiling rosette, **clear cable, emergency**
 length 5m, dark anthracite ceiling rosette, clear cable, **DALI**

[ZSD-H.D3-50.BP-3](#)
[ZSD-H.D3-50.TR-4](#)
[ZSD-H.D3-50.TR-5](#)

EXPLANATORY NOTES

for order code assembly

1	2	3	4	5	6
ZSC	-	K B3	-	50 .	TP - 5

1	TYPE OF SUSPENSION				
ZSA	ceiling solid suspension	ZVA	built-in solid suspension	ZLA	solid suspension for feeding track
ZSB	ceiling one-string adjustable suspension	ZVB	built-in one-string adjustable suspension	ZLB	one-string adjustable suspension for f. track
ZSC	ceiling three-string adj. susp. with rosette	ZVD	built-in two-string adjustable suspension	ZLD	two-string adjustable suspension for f. track
ZSD	ceiling two-string adjustable suspension	ZVE	built-in four-string adjustable suspension	ZLL	cable suspension for feeding track
ZSE	ceiling four-string adjustable suspension	ZVL	built-in cable suspension		
ZSF	ceiling four-string adj. susp. with rosette	ZVM	built-in three-string adjustable suspension		
ZSL	ceiling cable suspension				
ZSM	ceiling three-string adjustable suspension				
2	SUSPENSION MODIFICATIONS				
K	metal ceiling rosette	R	for attachment to ceiling winch	S	for higher load
P	plastic ceiling rosette	H	for high load		
3	COLOUR OF THE SUSPENSION / ROSETTE			3	COLOUR OF TRACK ADAPTER
	metal		plastic		
W3	white sand	B	black	B	black
S3	silver sand	W	white	G	gray
B3	black sand			W	white
D3	anthracite sand dark				
xx	optional colour according to RAL				
4	LENGTH OF SUSPENSION				
05	50cm	30	300cm	xx	optional length of suspension
10	100cm	40	400cm		
20	200cm	50	500cm		
5	COLOUR OF THE SUSPENSION				
	PVC		textile		
WP	white	WT	white		
BP	black	BT	black		
TP	transparent	xT	optional colour on request		
6	CONNECTION OF LUMINAIRE				
	3 - conductors		4 - conductors		5 - conductors
3	non-dimmable constant current driver non-dimmable constant voltage driver phase dimmable dimmable using push-button on luminaire dimmable Casambi (Bluetooth)	4	emergency 1h emergency 3h electronic address module dimmable using button 230V dimmable with CORRIDOR function two-circuit connection	5	dimmable analog 1-10V dimmable DALI dimmable Tunable white DALI dimmable DSI three-circuit connection