



Z844

LED pendant light fittings - multisource system

light fitting with integrated electronic control gears for central light source and 3 spotlights LED COIN 111 COB - INSERT modules, that are ordered separately • optional colour of COIN 111 COB cover ring black, white or RAL on request • housing from powder painted aluminium profile • colour option • optional beam angle • rated median operational life-time of luminaire 50 000h L70/B50 at Ta = 25°C • Standard Deviation Colour Matching MacAdam 2-step • double circuit connection • suspension ordered separately




LED COIN 111 COB B



Order code	Pict.	Light source	Power	Kg *
Z844	a	COIN 111 COB	max. 4x42W	4,3 kg

* weight including inserts


Example of order code assembly (floorplan - view from the ceiling)



BASE light fitting

1x **BASE** Z844 for 4 inserts
- light fitting anthracite sand dark


Z844/D3



Light sources

1x **INSERT** C009 - **position A**
1x **INSERT** C009 - **position B**
1x **INSERT** C009 - **position C**
1x **INSERT** C009 - **position D**
- spotlights COIN 111 COB

C009cBCI.142/24B (A)
C009cBCI.142/40B (B)
C009cBCI.142/40B (C)
C009cBCI.142/60B (D)



- W3
- S3
- D3
- B3



230V-50Hz

PDF Accessories



ZSD-H page 755 ZSP* mount. accessories

* needs to be specified!

C009

LED pendant light fitting - insert COIN 111 COB


INSERT with light source COIN 111 COB and control gear - optional colour of COIN 111 COB cover ring black, white or RAL on request - rated median operational life-time of luminaire 50 000h L70/B50 at Ta = 25°C - Standard Deviation Colour Matching MacAdam 2-step



B




W



Order code	Angle	Power	Flux	Tc	Ra
C009cBII.108/..	24/40/60	1 x 8 W	890 lm	2700 K	≥ 90
C009cBWI.108/..	24/40/60	1 x 8 W	900 lm	3000 K	≥ 90
C009cBCI.108/..	24/40/60	1 x 8 W	950 lm	4000 K	≥ 90
C009cBII.110/..	24/40/60	1 x 10 W	1070 lm	2700 K	≥ 90
C009cBWI.110/..	24/40/60	1 x 10 W	1090 lm	3000 K	≥ 90
C009cBCI.110/..	24/40/60	1 x 10 W	1150 lm	4000 K	≥ 90
C009cBII.114/..	24/40/60	1 x 14 W	1440 lm	2700 K	≥ 90
C009cBWI.114/..	24/40/60	1 x 14 W	1480 lm	3000 K	≥ 90
C009cBCI.114/..	24/40/60	1 x 14 W	1560 lm	4000 K	≥ 90
C009cBII.120/..	24/40/60	1 x 20 W	1990 lm	2700 K	≥ 90
C009cBWI.120/..	24/40/60	1 x 20 W	2050 lm	3000 K	≥ 90
C009cBCI.120/..	24/40/60	1 x 20 W	2160 lm	4000 K	≥ 90
C009cBII.128/..	24/40/60	1 x 28 W	2700 lm	2700 K	≥ 90
C009cBWI.128/..	24/40/60	1 x 28 W	2780 lm	3000 K	≥ 90
C009cBCI.128/..	24/40/60	1 x 28 W	2930 lm	4000 K	≥ 90
C009cBII.136/..	24/40/60	1 x 36 W	3360 lm	2700 K	≥ 90
C009cBWI.136/..	24/40/60	1 x 36 W	3460 lm	3000 K	≥ 90
C009cBCI.136/..	24/40/60	1 x 36 W	3650 lm	4000 K	≥ 90
C009cBII.142/..	24/40/60	1 x 42 W	3800 lm	2700 K	≥ 90
C009cBWI.142/..	24/40/60	1 x 42 W	3910 lm	3000 K	≥ 90
C009cBCI.142/..	24/40/60	1 x 42 W	4120 lm	4000 K	≥ 90

The shown value of luminous flux is useful luminous flux in solid angle 90°. The value depends on the beam angle of the light source.



LED COIN 111 COB



230V-50Hz

Dimmable version of insert

B / C / D / T

Example of order code assembly: **dimmmable DALI**

C009cBCD.128/24B

Optional beam angle

24 / 40 / 60

Example of order code assembly: **LED source with beam angle 24°**

C009cBCI.128/24B

Optional colour of COIN 111 COB covering ring

B / W

Example of order code assembly: **black ring COIN 111 COB**

C009cBCI.128/24B

EXPLANATORY NOTES

for order code assembly

1	2	3	4	5	6	7	8	9	10	11			
V	299	s	LW	DN	.	124	A	/	HD	A3	.	W3	B

1	MOUNTING CATEGORY			2	PRODUCT CODE		3	CONFIGURATION OF LIGHT FITTING				
V	recessed	L	track	299	type marking of light fitting		s	control gear on cable (part of l. fitting)				
S	ceiling	Z	pendant	014	type marking of insert		c	control gear in luminaire (part of l. fitting)				
N	wall	C	insert of fitting	etc.			a	control gear in adapter (part of l. fitting)				
F	floor						r	control gear in rosette (part of l. fitting)				
							-	without control gear				
4	TYPE OF LIGHT SOURCE (SOCKET)											
Q0	LED PAR16 (GU10)			E2	LED A60, A65 (E27)		E2	LED PAR20, 30, 38 (E27)				
4a	TYPE OF LED LIGHT SOURCE			4b	CHROMATICITY OF LED SOURCE		4b	SPECTRUM OF LED SOURCE				
A	LED COIN 111 COB, COIN 111 AC Ra >80			I	warm white "interna" (2700 K)		R	spectrum for meat and sausages				
B	LED COIN 111 COB Ra >90			W	warm white (3000 K)		Y	spectrum for pastry, delicatessen and cheese				
F	LED COIN 50 COB Ra >80			B	white (3500 K)		F	spectrum for fish				
G	LED COIN 50 COB Ra >90			C	cool white (4000 K)		Z	spectrum for fruits and vegetables				
N	LED COIN 35 COB Ra >80			D	daylight white (5000 K)		A	spectrum for art (Ra>97)				
P	LED COIN 35 COB Ra >90			S	cool daylight (6500 K)		V	spectrum for clothing, fashion				
L	LED panel Ra >80			K	tunable white - commercial (2700 K-6500 K)		P	spectrum for plant growth				
M	LED panel Ra >90			T	dim to warm (dimming to warm chroma.)							
C	LED COB Ra >80											
D	LED COB Ra >90											
H	LED COB Ra >97											
5	TYPE OF CONTROL GEAR						6	NUMBER AND OUTPUT OF LIGHT SOURCE				
	BASIC CONFIGURATION				EMERGENCY CONFIGURATION			NUMBER OF SOURCES, POWER OF FITTING				
I	non-dimmable constant current driver			N	emergency 1h		108	1 x 8 W				
U	non-dimmable constant voltage driver			H	emergency 3h		114	1 x 14 W				
A	dimmable analog 1-10V			F	emergency 1h with autotest		229	2 x 29 W				
D	dimmable DALI			G	emergency 3h with autotest		337	3 x 37 W				
T	dimmable DALI + touch-dim			Z	electronic address module		443	4 x 43 W				
C	dimmable with CORRIDOR function			P	central battery system							
S	dimmable DSI											
W	dimmable using push-button on luminaire											
L	phase dimmable											
X	dimmable Tunable white DALI											
B	dimmable Casambi (Bluetooth)											
7	TYPE OF REFLECTOR / OPTICS							TYPE OF DIFFUSER				
SP	spot - beam angle 10-20°			XW3	extra wide flood - 3x optics		HD	smooth divided				
MD	medium - beam angle 21-34°			XW2	extra wide flood - 2x optics		HG	powder coated gold (G1)				
FL	flood - beam angle 35-49°			MDG	medium - beam angle 21-34° (gold)		SB	powder coated black sand (B3)				
WF	wide flood - beam angle ≥ 50°			FLG	flood - beam angle 35-49° (gold)		SW	powder coated white sand (W3)				
XW	extra wide flood - beam angle ≥ 70°			HU	smooth UGR < 19		xx	optional RAL colour				
				MU	matt UGR < 19							
	TYPE OF EMERGENCY OPTICS											
OS	Open space			CR	Corridor							
	COLOUR OF OPTICAL SYSTEM				COLOUR OF COIN COB COVER RING		8	TYPE OF COVER GLASS				
B	black - matt			B	black		T1	tempered glass - clear				
W	white - matt			W	white		A1	acrylic glass - clear				
							A3	acrylic glass - opal				
							M1	acrylic microprisma - clear				
							M3	acrylic microprisma - opal				
9	TYPE OF COVER FILTER			9	COLOUR AND FINISH		10	SPECIAL VERSION				
F4	blue filter			W3	white sand interior/exterior		B	for assembly in concrete housing				
F5	red filter			S3	silver sand interior		F	for assembly in facade insulation				
F6	green filter			B3	black sand interior/exterior		KRP	for assembly in lamella ceilings				
F8	orange filter			D3	anthracite sand dark interior/exterior		P	for assembly in sheet metal ceilings				
FH	honeycomb louvre			S9	silver sand interior/exterior							
F9	linear spread lens*			xx	optional RAL colour							
	* for use with SP/MD reflector only											